



### Application

Insute is a high-performance insulation material specially developed for the construction sector and technical insulation. In addition to its highly insulating properties, the nanoporous foam is extremely stable and breathable. It forms individual insulation solutions for both old and new buildings. Outdoors and indoors, Insute offers completely new possibilities.

Wherever space is at a premium, complex building shapes have to be insulated and maximum insulation performance and stability are required, Insute shows its full performance as blow-in insulation or in products such as screed or insulating plaster.



### Technical Data

<b>Material</b>	Foamed acrylic copolymer
<b>Temperature range</b>	- 270 °C to + 80 °C
<b>Pore size</b>	Less than 0.1 µm
<b>Appearance</b>	Flakes *
<b>Bulk density</b>	70 - 100 kg/m <sup>3</sup>
<b>Pore structure</b>	Open-cell / breathable
<b>Mechanical stability</b>	High / non-abrasive

\* Individual sizes and sieve cuts available upon request.

### Insulation Values in Application

<b>Blow-in Insulation</b>	$\lambda < 0.025 \text{ W/mK}$
<b>Insulating Plaster</b>	$\lambda < 0.040 \text{ W/mK}$

### Environment & Sustainability

With no propellant emissions during production to climate-efficient usage and product recycling, we prioritize sustainability and circular economy. Insute insulation is durable and boasts low thermal conductivity values.

#### DISCLAIMER

This Technical Data Sheet contains strictly confidential and legally protected information. The contents of this document may only be used by the intended addressee. Any form of unauthorized publication, use, duplication or distribution to third parties is not permitted.

The document has been prepared exclusively for informational purposes and does not serve as a basis for any contractual obligations.

All information presented in this document are current as of the date provided. This document contains forward-looking statements. Because such statements involve risks and uncertainties, including, but not limited to, uncertainties related to SUMTEQ's current stage of technology and product development and dependence on collaborative arrangements, actual results and developments may differ materially.

